

Kobau RS-Papiervlies 130

Edition 03/2011



Type of crack / symbol



Field of application / properties

KOBAU RS-Papiervlies 130 is used in the field of surface remediation for finely structured substrates such as glass fabrics, stippling or for bridging cracks. For creating smooth indoor substrates ready for papering or painting.

Only or use inside.

In processed condition KOBAU RS-Papiervlies 130 is flame-retardant and corresponds to fire protection class B 1 in accordance with DIN 4102.

Processing

Prior to sizing the fleece, please check the finish of the product and only use products with the same batch number. In case of evident defects, the products will be replaced. Consequential costs will not be reimbursed.

The substrate must be dry, clean, solid, evenly absorbent and smooth. Remove old wallpapers and loose paint. Smoothen rough substrates using appropriate fillers. If required, prime absorbent substrates.

1) Use as paint supporting material:

For gluing, Ovalit GF or NP Power Granulat plus is recommended. Paste KOBAU RS-Papiervlies 130 with the pasting device and apply immediately or process in wall pasting technique. Paste the webs butt-jointed and press them against the substrate using a suitable paperhanging tool. Press projections against the substrate by means of a plastic spatula and trim with a cutter knife.

2) Use for substrate treatment:

For pasting, a filled dispersion adhesive such as Renomur Fertigspachtel innen is recommended. The adhesive is applied by means of a suitable toothed spatula on the surface.

Technical data

Quality	pulp/textile fibre
Colour	natural white
Stabilization	chemical
Specific weight according to DIN 53854	approx. 132 g/m ²
Thickness	approx. 320 µm
Max. longitudinal tensile force	> 108 N/15 mm
Max. transversal tensile force	> 80 N/15 mm
Max. transversal tensile force in wet condition	approx. 0.25 %
Air permeability	approx. 44 l/m ² s
Burst pressure	approx. 600 kPa
Hydrophoby	> 7 FI
Longitudinal stiffness	1.065 mg

3) Use as wallpaper substrate:

For bonding, at least special paste + approx. 20 % dispersion adhesive such as Ovalit T.

Delivery form

Roll dimensions: 1.00 m x 25 m
0.75 m x 25 m

Tools / embedding material

- Pasting device
- Toothed spatula
- Paperhanging tools

Required materials

Glass fabric adhesive, pasting according to manufacturer's specifications

Storage

in dry, cool and closed spaces

Caution

Perform subsequent work taking into account the corresponding instructions of the manufacturer.

Note